

SB-244 TGLU Series

Industrial Fanless Rugged Controller w/ Intel® 11th Gen. Tiger Lake Core i3 / i5 / i7 Processors



Features

- Intel® 11th Gen. Tiger Lake i3/i5/i7 processors
- 1 x DDR4 3200MHz SO-DIMM Slot, up to 32GB
- Support DP/HDMI display
- Support 4 Gigabit LAN ports
- Support Wide DC Input 10-36V
- Support Over-Voltage & Reversed Power Insertion Protection



HDMI



Over-voltage
Protection



USB 3.2



-20~60°C



Wide Voltage
Range



Reversed
Power Insertion
Protection

System

CPU	Intel® Tiger Lake Core i3 / i5 / i7 processors
Memory	1 x DDR4 SO-DIMM socket, supporting 3200 MHz SDRAM up to 32GB
Chipset	Integrated in CPU
Graphics	Integrated Intel® UHD graphics for 11 th gen processor
LAN Chipset	1 x Intel I219-LM GbE PHY 3 x Intel I210AT GbE controllers
Watchdog Timer	1~255 levels reset

Storage

Device	1 x M.2 M Key 2242 slot (SATA signals) 1 x SATA 3.1 (2.5" Drive bay) *CTOS is available
--------	---

Audio

Type	1 x Audio(Line-out & Mic-in) (Chipset ALC888S/897)
------	---

Power System

Power Input	10-36V DC, 2-pin phoenix connector
-------------	------------------------------------

OS

Windows 10/11, Ubuntu 22.04

Qualification

Certification	CE, FCC
---------------	---------

External I/O

Serial Ports	4 x RS232/422/485 (default RS232) with auto flow control
USB Ports	3 x USB3.2 3 x USB2.0
LAN	4 x RJ45
Video Ports	2 x HDMI (Max Resolution: 4096x2304@60Hz) 1 x DP (Max Resolution: 4096x2304@60Hz)
Power Button	1 x Power button w/ LED
Remote On/Off	1 x SW

Internal I/O

Expansion Slot	1 x full-size mPCIe 1x M.2 E Key 2203 slot (PCIe x1 / USB2.0 Signals)
SIM Card	1 x SIM card socket for 3G/4G module
USB 2.0 Ports	2 x USB2.0 by Pin head
COM Ports	2 x RS232 by Pin head
GPIO	1 x 8bit programmable GPIO pin header (3.3V / 5V Jumper Voltage adjustable)

Mechanical


Construction	Aluminum alloy
Mounting	Wall-mount VESA-mount (optional) Din Rail (optional, Composition: SB-244-VESA-MOUNT + SPA BOX PC DIN RAIL KIT)
Dimension (W x H x D)	224 x 140 x 49.2 mm
Weight	1.6kg

Environmental

Operating Temp.	-20 ~ 60°C (-4 ~ 140°F), ambient w/ air flow (WT RAM & SSD)
Storage Temp.	-40 ~ 85°C (-40 ~ 185°F)
Operating Humidity	5 ~ 95% @ 40°C (non-condensing)
Vibration	5~500Hz, 2Grms operation
Shock	Operation: 10G@11ms Non-operation: 30G@11ms

*CTOS means Configure-to-Order Service.

Dimensions



Packing List

SB-244-111XXXX	1 pcs BOX PC
Thermal PAD	2 pcs for Memory, 1 pcs for M.2 2242
2-pin terminal block	1 pcs 5mm for Power-input, 1 pcs 3.5mm for Remote on-off SW
22-pin SATA & Power cable	150mm, 1 pcs
Screw Package	1 pcs

Ordering Information

SB-244-11115G4	Barebone Fanless System with Core i3-1115G4, 4 x LAN, 4 x COM(up to 6), 6 x USB, 1 x HDMI, 1 x DP, DC10-36V power input
SB-244-11115G4-R8S128	Fanless System with commercial 8GB RAM & 128GB SSD, Core i3-1115G4, 4 x LAN, 4 x COM(up to 6), 6 x USB, 1 x HDMI, 1 x DP, DC10-36V power input
SB-244-11135G7	Barebone Fanless System with Core i5-1135G7, 4 x LAN, 4 x COM(up to 6), 6 x USB, 2 x HDMI, 1 x DP, DC10-36V power input
SB-244-11135G7-R8S128	Fanless System with commercial 8GB RAM & 128GB SSD, Core i5-1135G7, 4 x LAN, 4 x COM(up to 6), 6 x USB, 2 x HDMI, 1 x DP, DC10-36V power input
SB-244-11165G7 (OEM Request)	Barebone Fanless System with Core i7-1165G7, 4 x LAN, 4 x COM(up to 6), 6 x USB, 2 x HDMI, 1 x DP, DC10-36V power input
SPA BOX PC DIN RAIL KIT	DIN Rail Bracket w/Screw, 35mm W25, 25X47.8mm
SB-244-VESA-MOUNT	VESA BRACKET w/ DIN-Rail screw hole, SECC, Gray Paint, 224 x 130 x 10.5mm, DIN-Rail mount (SB-244-VESA-MOUNT + SPA BOX PC DIN RAIL KIT) for SB-244-TGLU, SB-244-1NXXX
8bit GPIO Cable	250mm, DB9M TO HSG2 x 6P(2.0), 8bit GPIO, W/O BRACKET, W/SCREW
2 x RS232 Y Cable	100mm, DB9M x 2 TO HSG2 x 3P(2.0), RS232, W/O BRACKET, W/SCREW
PAC-120W-FSP-SPA-US R1.0	AC/DC Adapter Kit (w/ UKCA), 19V, 120W, 2 WIRE w/ US POWER CORD
PAC-120W-FSP-SPA-EU R1.0	AC/DC Adapter Kit (w/ UKCA), 19V, 120W, 2 WIRE w/ EU POWER CORD
PAC-120W-FSP-SPA-UK R1.0	AC/DC Adapter Kit (w/ UKCA), 19V, 120W, 2 WIRE w/ UK POWER CORD
PAC-120W-FSP-SPA-IN R1.0	AC/DC Adapter Kit (w/ UKCA), 19V, 120W, 2 WIRE w/ IN POWER CORD
PAC-120W-FSP-SPA-JP R1.0	AC/DC Adapter Kit (w/ UKCA), 19V, 120W, 2 WIRE w/ JP POWER CORD