

SP-151C TGLU Series

Industrial Fanless 15.6" Panel PC w/ Intel® 11th Tiger Lake U Series Processor



Features

- 11th Generation Intel® Core™ i5/i3 Processor (Tiger Lake)
- 15.6 inches LCD with LED backlight, front panel support IP66
- Industrial-grade 10 points project capacitive touch screen
- 1 x DDR4 3200MHz SO-DIMM Slot, up to 32GB
- Support 1 x 2.5 GbE and 2 x GbE LAN
- Support remote ON-OFF
- Grounding protection for product shell
- Support 1 x 2.5 inches HDD/SSD expansion
- Support standard VESA and panel mount
- Support 10-36V Wide DC Input
- Support Over-voltage and Reserved Power Insertion Protection



HDMI



Over-voltage
Protection



USB 3.1



-10~50°C



Wide Voltage
Range



Reversed
Power Insertion
Protection

System

CPU	11 th Generation Intel® Core™ i5/i3 Processor (Tiger Lake U series)
Memory	1 x DDR4 SO-DIMM socket, supporting 3200 MHz SDRAM up to 32GB *CTOS is available
Chipset	Integrated in CPU
Graphics	Integrated Intel® UHD Graphics
LAN Chipset	1 x Intel® i226-V 2.5GbE controller 2 x Intel® i210-AT GbE controllers
Watchdog Timer	1~255 levels reset

Storage

Device	1 x M.2 M Key 2242 Slot (SATA signal) 1 x 22pin SATA 3.0 Slot for 2.5" HDD/SSD drive bay *CTOS is available
--------	---

Audio

Type	1 x Audio (Line-out & Mic-in 2 in 1) (Chipset ALC888S)
Speaker	2 x 4Ω 3W speakers

LCD Display

Size/Type	15.6 inches TFT LCD Panel
Max. Resolution	1920(H) x 1080(V)
Ratio	16:9
Luminance	350 nits
Contrast Ratio	800:1
Backlight Type	LED
Backlight Lifetime	50,000 Hrs
Touch Type	10 points project capacitive touch screen
Touch	35,000,000 times
View Angle	CR ≥ 10, 178°(H) / 178°(V)

Power System

Power Input	10~36V DC, 2-pin Phoenix connector
-------------	------------------------------------

OS

Windows 10/11, Ubuntu 22.04

Qualification

Certification	CE, FCC
External I/O	
Serial Ports	2 x RS232/422/485 (COM1/2) with DB9 2 x RS232/RS485, 2 x RS232 with 12-pin Phoenix connector
USB Ports	4 x USB 3.1
LAN	3 x RJ45
Video Ports	1 x HDMI (up to 4096 x 2160@60Hz)
Remote On-Off	1 x Remote On/Off Switch

Internal I/O

Expansion	1 x full-size MiniPCle (PCle / USB2.0 signal support) 1 x M.2 E Key 2230 slot (PCle / USB2.0 signal supported) 1 x SIM socket 1 x 8bit GPIO
-----------	--

Mechanical


Front Panel	Aluminum alloy
Heat-Sink	Aluminum alloy
Rear Cover	SECC
Mounting	Panel mount, Wall mount and VESA-mount (100 x 100 mm)
Dimension (W x H x D)	395(W) x 245.5(H) x 59(D)mm
Cut out	387 x 237.5mm
Weight	4.54 Kg
Ingress Protection	Front panel IP66

Environmental

Operating Temp.	-10 ~ 50°C (14 ~ 122°F), ambient w/ air flow (WT RAM & SSD)
Storage Temp.	-40 ~ 70°C (-40 ~ 158°F)
Operating Humidity	5 ~ 95% @40°C (non-condensing)
Vibration	5~500Hz, 2Grms operation
Shock	Operation: 10G@11ms Non-operation: 30G@11ms

*CTOS means Configure-to-Order Service.

Dimensions



Packing List

SP-151C-111XXXXX	1 pcs Panel PC
Panel Hook	4 pcs in 1package
Thermal Pad	1 pcs, for M.2 2242, 1 pcs for Memory
2-pin terminal block	1 pcs 5mm for Power-input, 1 pcs 3.5mm for Remote on-off SW
DIP-12 Terminal block	1 pcs for serial ports (COM3~6)
Screw package	1 pcs

Ordering Information

SP-151C-11135G7	15.6"(16:9) Panel PC with Intel® 11th Gen Core™ i5-1135G7 2.4G processor
SP-151C-11135G7-R8S128	15.6"(16:9) Panel PC with commercial 8GB RAM & 128GB SSD, Intel® 11th Gen Core™ i5-1135G7 2.4G processor
SP-151C-11115G4	15.6"(16:9) Panel PC with Intel® 11th Gen Core™ i3-1115G4 3.0G processor
SP-151C-11115G4-R8S128	15.6"(16:9) Panel PC with commercial 8GB RAM & 128GB SSD, Intel® 11th Gen Core™ i3-1115G4 3.0G processor
PAC-120W-FSP-SPA-US R1.0	AC/DC Adapter Kit (w/ UKCA), 19V,120W, 2 WIRE w/ US POWER CORD
PAC-120W-FSP-SPA-EU R1.0	AC/DC Adapter Kit (w/ UKCA), 19V,120W, 2 WIRE w/ EU POWER CORD
PAC-120W-FSP-SPA-UK R1.0	AC/DC Adapter Kit (w/ UKCA), 19V,120W, 2 WIRE w/ UK POWER CORD
PAC-120W-FSP-SPA-IN R1.0	AC/DC Adapter Kit (w/ UKCA), 19V,120W, 2 WIRE w/ IN POWER CORD
PAC-120W-FSP-SPA-JP R1.0	AC/DC Adapter Kit (w/ UKCA), 19V,120W, 2 WIRE w/ JP POWER CORD

