


EmCOMe-i93M0

12th Intel® Core™ i7-12800HE/ i5-12600HE/ i3-12300HE Processor COM Express® Type 6 Basic CPU Module



Features

- Soldered onboard 12th Alder Lake Intel® Core™ i7-12800HE/ i5-12600HE/ i3-12300HE Processor
- Intel® I226 Series PCIe 2.5GbE Ethernet controller
- Dual Channels 24-bit LVDS, Analog RGB and 3 x DDI ports
- Support Max. 4 independent displays
- 8.5V~20V Wide Range Voltage Input
- **Wide Range Operating Temp.: -40 ~ 85°C**

System

	Soldered onboard 12 th Generation Intel® Core™
CPU	<ul style="list-style-type: none"> - i7-12800HE 3.5GHz(E-core)/ 4.6GHz (P-core) - i5-12600HE 3.3GHz(E-core)/ 4.5GHz (P-core) - i3-12300HE 3.3GHz(E-core)/ 4.3GHz (P-core) - i7-1270PE 3.3GHz(E-core)/4.5GHz(P-core) - i5-1250PE 3.2GHz(E-core)/4.4Ghz(P-core) - i3-1220PE 3.1GHz(E-core)/4.2Ghz(P-core)
Memory	2 x DDR5 SO-DIMM sockets
BIOS	AMI UEFI BIOS
Watchdog Timer	1~255 levels reset
I/O	
USB Port	12 x USB ports: <ul style="list-style-type: none"> - 8 x USB 2.0 ports - 4 x USB 3.2 ports
Serial Port	2 x UART ports (RX/TX only)
Expansion Bus	1 x PCIe8 lanes(H series only) 2 x PCIe4 lanes 8 x PCIe1 lanes (or 1 x PCIe4 + 4 x PCIe x1) I ² C, GPIO, SMBUS, LPC Interface
Storage	2 x SATA ports with 600MB/s HDD transfer rate 1 x NVMe BGA SSD(optional)(Share PEG 1 x PCIe4)
Ethernet Chipset	1 x Intel®i226 series PCIe 2.5GbE Ethernet controller
Audio	HD audio link
TPM	Supports TPM 2.0
Display	
Graphic Chipset	Integrated Intel® Iris Xe or UHD Graphics (depends on CPU SKU)
Graphic Interface	1 x Dual Channel 24-bit LVDS (default) or eDP 1 x Analog RGB port 3 x DDI ports

OS support


Windows 10 64-bit
Windows 11 64-bit
Linux: Ubuntu

Mechanical & Environmental

Power Requirement	8.5V~20V wide range voltage input, +5VSB
Power Consumption	TBD
Operating Temp.	-40 ~ 85°C (-40 ~ 185°F)
Operating Humidity	10 ~ 95% @ 85°C (non-condensing)
Dimensions (L x W)	95 x 125 mm (3.7" x 4.9")



Block Diagram



Ordering Information

EmCOMe-i93M0-WT-12800HE	12 th Gen Intel Core i7-12800HE WT COMe Basic Type 6 CPU Module, -40~85°C
EmCOMe-i93M0-WT-12600HE	12 th Gen Intel Core i5-12600HE WT COMe Basic Type 6 CPU Module, -40~85°C
EmCOMe-i93M0-WT-12300HE	12 th Gen Intel Core i3-12300HE WT COMe Basic Type 6 CPU Module, -40~85°C
EmCOMe-i93M0-WT-1270PE	12 th Gen Intel Core i7-1270PE WT COMe Basic Type 6 CPU Module, -40~85°C
EmCOMe-i93M0-WT-1250PE	12 th Gen Intel Core i5-1250PE WT COMe Basic Type 6 CPU Module, -40~85°C
EmCOMe-i93M0-WT-1220PE	12 th Gen Intel Core i3-1220PE WT COMe Basic Type 6 CPU Module, -40~85°C
HS-93M0-C1	Heat sink 95*125mm,W/FAN+PAD
PBC-1705	COM Express type 6 carrier board (ATX form factor)
CBK-03-1705-00	Cable kit 1 x SATA cable 2 x COM Flat cables