


EmCOMe-i94U0



13th Intel® Core™ i7-1365UE/ i5-1335UE/ i3-1315UE/ U300E Processor COM Express® Type 6 Compact CPU Module



Features

- Soldered onboard 13th Raptor Lake Intel® Core™ i7-1365UE/ i5-1335UE/ i3-1315UE/ U300E Processor
- Intel® I226 Series PCIe 2.5 GbE Ethernet controller
- Dual Channels 24-bit LVDS, Analog RGB and 3 x DDI ports
- Support Max. 4 independent displays
- 8.5V~20V Wide Range Voltage Input
- **Wide Range Operating Temp.: -40 ~ 85°C**

System

CPU	Soldered onboard 13 th Generation Intel® Core™ - i7-1365UE 3.7GHz(E-core)/ 4.9GHz (P-core) - i5-1335UE 3.4GHz(E-core)/ 4.6GHz (P-core) - i3-1315UE 3.3GHz(E-core)/ 4.5GHz (P-core) - Intel® U300E 3.2GHz(E-core)/ 4.3GHz (P-core)
Memory	2 x DDR5 SO-DIMM sockets
BIOS	AMI UEFI BIOS
Watchdog Timer	1~255 levels reset
I/O	
USB Port	12 x USB ports: - 8 x USB 2.0 ports - 4 x USB 3.0 ports
Serial Port	2 x UART ports (RX/TX only)
Expansion Bus	2 x PCIe4 lanes 8 x PCIe1 lanes (or 1 x PCIe4 + 4 x PCIe1) I ² C, GPIO, SMBUS, LPC Interface
Storage	2 x SATA ports with 600MB/s HDD transfer rate 1 x NVMe SSD (Optional)(Share PEG 1 x PCIe4)
Ethernet Chipset	1 x Intel® i226 Series PCIe 2.5 GbE Ethernet controller
Audio	HD audio link
TPM	Supports TPM 2.0

Display


Graphic Chipset	Integrated Intel® Iris Xe or UHD Graphics (depends on CPU SKU)
Graphic Interface	1 x Dual Channel 24-bit LVDS (default) or eDP 1 x Analog RGB port 3 x DDI ports

OS support


Windows 10 64-bit
Windows 11 64-bit
Linux: Ubuntu

Mechanical & Environmental

Power Requirement	8.5V~20V wide range voltage input, +5VSB
Power Consumption	2.1A@12V 1.3A@20V (i7-1365UE CPU Module only)
Operating Temp.	-40 ~ 85°C (-40 ~ 185°F)
Operating Humidity	10 ~ 95% @ 85°C (non-condensing)
Dimensions (L x W)	95 x 95 mm (3.7" x 3.7")



Block Diagram



Ordering Information

EmCOMe-i94U0-WT-1365UE	13 th Gen Intel® Core™ i7-1365UE WT COMe Compact Type 6 CPU module, -40 ~ 85°C
EmCOMe-i94U0-WT-1335UE	13 th Gen Intel® Core™ i5-1335UE WT COMe Compact Type 6 CPU module, -40 ~ 85°C
EmCOMe-i94U0-WT-1315UE	13 th Gen Intel® Core™ i3-1315UE WT COMe Compact Type 6 CPU module, -40 ~ 85°C
EmCOMe-i94U0-WT-U300E	13 th Gen Intel® U300E WT COMe Compact Type 6 CPU module, -40 ~ 85°C

Optional Accessories

HS-93U0-C1	Heat sink with Fan (95x95x37.6mm)
HS-93U0-F1-T	Heat spreader, threaded standoffs (bore hole) (95x95x11mm)
HS-93U0-F1-NT	Heat spreader, non-threaded standoffs (bore hole) (95x95x11mm)
PBE-1705	COM Express® Type 6 carrier board (ATX form factor)
	Cable kit
CBK-03-1705-00	1 x SATA cable 2 x COM Flat cables